



96K SERIES
BI-PARTING SLIDING DOORS
FULL BREAKOUT
NARROW STILE
WITH THRESHOLD

SO-SX-SX-SO

7350 West Wilson Ave.
Harwood Heights, IL. 60706-4786

Phone: (800) 543-4635
Fax: (708) 867-0291

www.doromatic.com

89501REV C
JUNE 18, 2003 ECN 00966

NOTE:

STANDARD PACKAGE:
OPERATOR, NARROW STILE DOORS & SIDELITES,
FRAMES, 2" MUNTINS, WEATHERSTRIPPING, EMERGENCY
BREAKOUT ON "SX" DOORS & "SO" PANELS, STANDARD
LOCK CYLINDER WITH THUMBTURN, 4-POSITION SWITCH,
2-POSITION KEYSWITCH, MOTION SENSOR, PRESENCE
SENSOR, DOOR HOLDING BEAMS, ANTI-JAR WHEELS, 1/4"
GLAZING SYSTEM, AND ONE PIECE 1/2" X 7-1/2"
THRESHOLD - JAMB TO JAMB.

STANDARD FINISH:
CLEAR ANODIZED - US28
DARK BRONZE ANODIZED - DC13
SPECIAL COLORS ARE AVAILABLE.

- * MAX. GLASS THICKNESS IS 5/8" IN "SO" SIDELITE AND
1" IN "SX" DOORS (GLASS STOP HEIGHT = 1-1/8").
- * TRANSOM OPTIONAL - MAX. HEIGHT 6'-0"
TOP OF HEADER TO TOP OF TRANSOM.
CONSULT FACTORY FOR LARGER SIZES.
- * TRANSOM FLUSH GLAZING OTHER THAN 1/4" GLASS
HAS SURFACE APPLIED GLASS STOPS.
- * ALL WRITTEN DIMENSIONS ARE TO TAKE
PREFERENCE OVER SCALED DIMENSIONS.
- * SIZES LARGER THAN 14'-0" - CONSULT WITH FACTORY.
- * ALL ANSI DECALS ARE PROVIDED.

OVERALL FRAME WIDTH (A)	DOOR OPENING WIDTH (B)	DOOR/PANEL WIDTH (C)	MASONRY OPENING WIDTH (D)
8'-3 1/2" (MIN.)	42"	25"	8'-4"
10'-0"	48"	30"	10'-0 1/2"
12'-0"	60"	36"	12'-0 1/2"
14'-0" (MAX.)	72"	42"	14'-0 1/2"

