



96K SERIES
 BI-PARTING SLIDING DOORS
 MID-PANEL PANIC EXIT DEVICE
 FULL BREAKOUT
 NARROW STILE
 WITH THRESHOLD

SO-SX-SX-SO

7350 West Wilson Ave.
 Harwood Heights, IL 60706-4786

Phone: (800) 543-4635
 Fax: (708) 867-0291

www.doromatic.com

89513REV D
 JUNE 18, 2003 ECN 00966

NOTE:

STANDARD PACKAGE:
 OPERATOR, NARROW STILE DOORS & SIDELITES, FRAMES,
 4" MUNTINS IN "SO" SIDELITES, WEATHERSTRIPPING, EMERGENCY
 BREAKOUT ON "SO" PANEL, MID-PANEL PANIC EXIT DEVICE
 IN 4" MUNTIN ON "SX" DOORS, HYDRAULIC CLOSERS IN "SX"
 DOORS AND "SO" SIDELITES, FAIL SECURE ELECTRIC LOCK,
 4-POSITION SWITCH, 2-POSITION KEYSWITCH, MOTION SENSOR,
 PRESENCE SENSOR, DOOR HOLDING BEAMS, ANTI-JAR WHEELS,
 1/4" GLAZING SYSTEM, AND ONE PIECE 1/2" X 7-1/2"
 THRESHOLD - JAMB TO JAMB.

STANDARD FINISH:
 CLEAR ANODIZED - US28
 DARK BRONZE ANODIZED - DC13
 SPECIAL COLORS ARE AVAILABLE.
 PANIC DEVICES ARE AVAILABLE IN STANDARD FINISH, DC35,
 AND CHAMPAGNE.

- * DOOR WIDTHS OF 42" OR GREATER REQUIRE A 24" PANIC DEVICE. (LESS THAN 42" BUT GREATER THAN 30", REQUIRE 21" PANIC DEVICE).
- * MAX. GLASS THICKNESS IS 5/8" IN "SO" SIDELITES, AND 1" IN "SX" DOORS (GLASS STOP HEIGHT = 1-1/8").
- * TRANSOM OPTIONAL - MAX. HEIGHT 6'-0" TOP OF HEADER TO TOP OF TRANSOM. CONSULT FACTORY FOR LARGER SIZES.
- * TRANSOM FLUSH GLAZING OTHER THAN 1/4" GLASS HAS SURFACE APPLIED GLASS STOPS.
- * ALL WRITTEN DIMENSIONS ARE TO TAKE PREFERENCE OVER SCALED DIMENSIONS.
- * SIZES LARGER THAN 14'-0" - CONSULT WITH FACTORY.
- * ALL ANSI DECALS ARE PROVIDED.

OVERALL FRAME WIDTH (A)	DOOR OPENING (B)	DOOR/PANEL WIDTH (C)	MASONRY OPENING WIDTH (D)
10'-0" (MIN.)	48"	30"	10'-0 1/2"
12'-0"	60"	36"	12'-0 1/2"
14'-0" (MAX.)	72"	42"	14'-0 1/2"

