



96K SERIES
 BI-PARTING DOORS
 PADDLE PANIC EXIT DEVICE
 FIXED SIDELITES
 NARROW STILE
 WITH THRESHOLD

0-SX-SX-0

7350 West Wilson Ave.
 Harwood Heights, IL 60706-4786

Phone: (800) 543-4635
 Fax: (708) 867-0291

www.doromatic.com

89514REV C
 JUNE 18, 2003 ECN 00966

NOTE:

STANDARD PACKAGE:
 OPERATOR, NARROW STILE DOORS & SIDELITES, FRAMES,
 2" MUNTINS, WEATHERSTRIPPING, PADDLE PANIC EXIT DEVICE
 ON LEADING STYLE OF "SX" DOOR, HYDRAULIC CLOSERS ON
 "SX" DOORS, 4-POSITION SWITCH, 2-POSITION KEYSWITCH,
 MOTION SENSOR, PRESENCE SENSOR, DOOR HOLDING BEAMS,
 ANTI-JAR WHEELS, AND ONE PIECE 1/2" X 7-1/2" THRESHOLD
 JAMB TO JAMB.

STANDARD FINISH:
 CLEAR ANODIZED - US2B
 DARK BRONZE ANODIZED - DC13
 SPECIAL COLORS ARE AVAILABLE.

- * PANIC DEVICE MUST HAVE APPROVAL OF CODE OFFICIALS.
- * MAX. GLASS THICKNESS IS 1" (GLASS STOP HEIGHT = 1-1/8").
- * TRANSOM OPTIONAL MAX. HEIGHT 6'-0" TOP OF HEADER TO TOP OF TRANSOM. CONSULT FACTORY FOR LARGER SIZES.
- * TRANSOM FLUSH GLAZING OTHER THAN 1/4" GLASS HAS SURFACE APPLIED GLASS STOPS.
- * ALL WRITTEN DIMENSIONS ARE TO TAKE PREFERENCE OVER SCALED DIMENSIONS.
- * SIZES LARGER THAN 14'-0" - CONSULT WITH FACTORY.
- * ALL ANSI DECALS ARE PROVIDED.

OVERALL FRAME WIDTH (A)	DOOR OPENING (B)	DOOR/PANEL WIDTH (C)	MASONRY OPENING WIDTH (D)
8'-3 1/2" (MIN.)	42"	25"	8'-4"
10'-0"	48"	30"	10'-0 1/2"
12'-0"	60"	36"	12'-0 1/2"
14'-0" (MAX.)	72"	42"	14'-0 1/2"

