



96K SERIES
 BI-PARTING SLIDING DOORS
 PADDLE PANIC EXIT DEVICE
 FIXED SIDELITES
 NARROW STILE
 WITHOUT THRESHOLD

0-SX-SX-0

7350 West Wilson Ave.
 Harwood Heights, IL. 60706-4786

Phone: (800) 543-4635
 Fax: (708) 867-0291

www.doromatic.com

89518REV
 JUNE 18, 2003 ECN 00966

NOTE:
 STANDARD PACKAGE:
 OPERATOR, NARROW STILE DOORS & SIDELITES, FRAMES,
 2" MUNTINS, WEATHERSTRIPPING, PADDLE PANIC EXIT DEVICE
 ON LEADING STILE OF "SX" DOOR, HYDRAULIC CLOSERS IN
 "SX" DOORS, FAIL SECURE ELECTRIC LOCK, 4-POSITION SWITCH,
 2-POSITION KEYSWITCH, MOTION SENSOR, PRESENCE SENSOR,
 DOOR HOLDING BEAMS, ANTI-JAR WHEELS, AND 1/4" GLAZING
 SYSTEM.

STANDARD FINISH:
 CLEAR ANODIZED - US28
 DARK BRONZE ANODIZED - DC13
 SPECIAL COLORS ARE AVAILABLE.

* PANIC DEVICE MUST BE APPROVED BY CODE OFFICIAL.
 * MAX. GLASS THICKNESS IS 1".
 (GLASS STOP HEIGHT = 1-1/8").
 * TRANSOM OPTIONAL MAX. HEIGHT 6'-0" TOP
 OF HEADER TO TOP OF TRANSOM. CONSULT
 FACTORY FOR LARGER SIZES.
 * TRANSOM FLUSH GLAZING OTHER THAN 1/4" GLASS
 HAS SURFACE APPLIED GLASS STOPS.
 * ALL WRITTEN DIMENSIONS ARE TO TAKE
 PREFERENCE OVER SCALED DIMENSIONS.
 * SIZES LARGER THAN 14'-0" - CONSULT WITH FACTORY.
 * ALL ANSI DECALS ARE PROVIDED.

OVERALL FRAME WIDTH (A)	DOOR OPENING (B)	DOOR/PANEL WIDTH (C)	MASONRY OPENING WIDTH (D)
8'-3 1/2" (MIN.)	42"	25"	8'-4"
10'-0"	48"	30"	10'-0 1/2"
12'-0"	60"	36"	12'-0 1/2"
14'-0" (MAX.)	72"	42"	14'-0 1/2"

